

AWD FITTING & JOINT TAPE



PRODUCT DESCRIPTION

AWD Fitting & Joint Tape is recommended for the sealing, seaming, terminating, and connection of AWD Fittings and AWD geocomposite drainage products as referenced in AWD literature, including installation guides, CAD details, and technical bulletins. AWD Fitting & Joint Tape is designed for underground use and provides a strong bond that will not deteriorate over time in typical subsurface conditions.

AWD Fitting & Joint Tape has...

- 40 mil thick composite member,
- Reinforced polyolefin base, laminated to a polypropylene layer
- Adhesive-backed with removable release liner

| PHYSICAL PROPERTIES | TEST METHOD | UNIT OF MEASURE | Typical Value |
|---|---------------|-----------------|---------------|
| Tensile Strength Machine Direction (Force) Cross Direction (Force) | ASTM D751-95 | lbs | 130 |
| | | lbs | 124 |
| Trapezoidal Tear Strength Machine Direction (Force) Cross Direction (Force) | ASTM D4533-91 | lbs | 46 |
| | | lbs | 44 |
| Mullen Burst | ASTM D751-95 | psi | 180 |
| UV Exposure (2000 hours) | ASTM G154-98 | % | >90 |
| Permeability (MVTR) | ASTM E96-B | Perms | <0.075 |
| Recycled Content | CALCULATED | % | >45 |
| Roll Size | MEASURED | in x ft | 4 x 75 |